
# TRAPEZOID ALUMINUM SHELL RESISTOR

RAGH-2

RAGH 薄型鋁殼電阻器

FLAT TYPE METAL CLAD WIRE WOUND RESISTOR (GH Type)



外觀顏色 : Body Color 標示 : Marking

銀色 : Silver 文字 : Alphanumeric

## ■特性 Feature

◎精密型高額定功率

 $\ensuremath{\bigcirc}$  High power rating, and ultra precision.

◎可依客戶需求製作

 $\ensuremath{\bigcirc}$  Can be produced according to customer's request.

◎產品符合歐盟 RoHS 要求

#### ■料號編碼 Type composition

例 Example

RA	GH	400	J	10R0	S200
型名 Type	品名 Series	額定功率 Rated ower	誤差值 Tolerance	電阻值(Ω) Resistance	直線 Straight
	薄型	400:40W	F±1%	R100=0.1	S050:50mm
	GH	500:50W	G±2%	1R00=1	S200:200mm
		800:80W	J±5%	10R0=10	S350:350mm
			•	1000=100	SA00:1000mm

## ■額定 Ratings


Rated Power (W)	阻值範圍 Resistance Range (Ω)	誤差值 Tolerance	溫度係數 T.C.R.	最高使用電壓 Max. Working Voltage DC	最高過負荷電壓 Max. Overload Voltage DC	耐電壓 Dielectric Withstanding Voltage DC
40	0.1 ∼ 1K					1000V
50	0.1 ∼ 1K	F±1% G±2% J±5%	± 350ppm/°C	1000V	2000V	可訂製最高 3000V
80	0.1 ∼ 1K					Client request: Max.3000V






### ■額定溫度下降曲線圖 Derating curve

#### 例 Example




#### ■性能 Performance

試驗項目 Test Items	規格值 Performance Requirements	試驗方法 Test Methods	
短時間過負荷 Short time overload	±(2%+0.1Ω)	6.25 倍額定功率,5 秒 6.25 times the rated power for 5 seconds	
負荷壽命 Load life	±(5%+0.1Ω)	Rated voltageC for 1,000 hours 1.5hr ON / 0.5hr OFF Cycles	
耐濕性 Moisture resistance	±(1%+0.1Ω)	40℃,95% RH,240 小時 40℃, 95% RH for 240 hours	
溫度循環 Temperature cycle	±(1%+0.05Ω)	5 cycles for -25°C (30min); room temp. (30min) ~ +85°C (30min) room temp. (30min)	



**RAGH40W** 

# 61±1 54±1 \*\*\*



# 6±0.5 106±1 116±0.5 124±1

RAGH50W RAGH80W